

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N. 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O. Box 240. North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

CLIENT TEXTILE MANIA PL

560 SWAN STREET

TEST NUMBER : 7-578283 BY : 03/05/2011

RICHMOND VIC 3121

ISSUE DATE PRINT DATE

03/05/2011

ORDER NUMBER : 20536

SAMPLE DESCRIPTION Clients Ref: "#9843 EPIC"

Yarn Dye Dobby Fabric

Nominal Composition: Wool/Nylon

Colour: Khaki

End use: Upholstery

AS/NZS 1530.3-1999 MODIFIED NUMBER OF SAMPLES TESTED

Early Fire Hazard Guidance Test

This test is for Guidance only ____________________

A reduced number of specimens were tested to provide guidance only as to the likely performance of the product

李岳龙底:	S 24.3	.英语杂。	200	w.a -68		Spec	A 1 46 37		Spec	7	企艺 進法	18216	200	\$2.5£
	AUK.			13:15 (3:2)	表式重数		存在多数。						24	3-14-28-28
Igni	tabil	ity	ind	.ex∈∵		· 0		940	0		- 16 P	Ran	ପ€ଂ	0 - 20
學更多的	密生色素	4.2 Z.3	ê a Gris		医连维液		计数据的							
		常货的			72 C						5 7 6 2			****
Spre	ad of	F.	ame	Inde	6969	0	NA ANA	多多多点	0	W. C. W.	# * # #	Ran	ďΑ	0+10
F54.7		医多孢子		Dug gult	医阴道性腺			各提多多						
a filiatorija		### ##	14.55	16.50.5		33,340				1-4-3-4-4 1-4-3-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-	6 8 S		4.7	使手成甲 氏
Heat	Ftto 1	Mod	Tad	GY .	8008	. n n n	14 5 K	848 B	'n			Dan	ďΩ	0-10
	A CONTRACTOR OF THE	is desired				3 Y	Orani (Se		30.00			31.500	90	* * * * * * *
各身长窜。	高海區 拼	849 d		u aşa						28/43		多主流		
Cmale	a Dar			Index		3 m			18 8 % i			D-14-		0-10
										vi Willer			ye	o_{-} r_{o}
The	rest	ılts	-on 1	y apı	ilν t	to t	he si	oeci	men.	moun	oted	ลร		
Z (EZ) 7:			\$ 5.75.75		2/			5 5 5 5 5			4.50		1.2.3.4	5 10 Sec. 10

described in this report

Two specimens only were tested

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

Ignition is initiated by a pilot flame that is held near, but does not touch the specimen. A material that does not ignite during the standard test may ignite if contacted with a pilot flame during the test.

Each test specimen had an unattached backing of 4.5mm thick fibre reinforced cement board.

(CONTINUED NEXT PAGE)

Australian Wool Testing Authority Ltd Copyright - All Hights Reserved

Samples, and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. The above test results are designed to provide THE CLIENT WITH GUIDANCE INFORMATION ONLY.

This document shall not be reproduced except in full and shall be rendered void if amonded or altered.

This document, the name AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved in advance by the Managing Director of AWTA Ltd.

APPROVED SIGNATORY

A JACKSÓN B Sc (Hons) NAGING DIRECTOR

187442